

ZEUS 300-AB

2x100W @ 8ohm / 2x150W @ 4ohm Professional Class-AB Power Amplifier

ZEUS amplifiers always mean reliability and ruggedness. They were born for fixed installations or live applications of low-impedance professional sound systems, and offer RMS powers ranging from 100W to 1000W @ 80hm per channel. The series consists of 2-channel models, three of them in class AB; two in class H. Thus, these are equipment whose technologies are extensively tested and guarantee the highest

AB; two in class H. Thus, these are equipment whose technologies are extensively tested and guarantee the highest audio quality.

The difference from similar systems depends on the great

attention paid to the quality of the components (toroidal transformers, electrolytic capacitors, transistors and others) and to the efficiency of protections and limiter, all while always considering robustness, durability and safety of both internal circuitry and driven speakers.









PRODUCT DETAILS

Key features

Stereo/parallel/bridged-mono Modes	
Intelligent Cooling System	
2x 19" Rack Unit Chassis Design	
AB-Class traditional and reliable circuitry	
High-quality transformers and components	
Thermal, Short Circuit and Signal Protection	
Soft Start Function	

Specifications

Stereo Rated Output Power (THD=0.5%, 1kHz, both $2 \times 100 \text{W} \oplus 8\Omega$; $2 \times 150 \text{W} \oplus 4\Omega$ channels driven)

•	
Bridged Output Power	1 x 300W @ 8Ω
Input Sensitivity	0.775V / 1.0V / 1.4V
Input Impedance	20ΚΩ / 10ΚΩ
Frequency Response	20Hz - 20kHz ±0.3dB
Damping Factor	> 350
S/N Ratio	> 95dB
Amplifier Class	A/B
Power Requirements	230-250Vac - 50/60Hz
Power Consumption (average/max)	200W / 310W
Dimension (WxHxD)	483 x 340 x 88 mm (19.0 x 13.4 x 3.5 in)
Height	2 x 19" Rack Unit
Unit Weight	7.85 kg - 17.3 lbs.
Packing Size (WxHxD)	550 x 405 x 168 mm (21.6 x 15.9 x 6.6 in)
Carton Weight	9.45 kg - 20.8 lbs.