

ZEUS 900-AB

2 x 300W @ 8ohm, 2 x 450W @ 4ohm Professional Class-AB Power Amplifier

ZEUS amplifiers always mean reliability and ruggedness. They were born for fixed installations or live applications of low-impedance professional sound systems, and offer RMS powers ranging from 100W to 1000W @ 8ohm per channel.

The series consists of 2-channel models, three of them in class AB; two in class H. Thus, these are equipment whose technologies are extensively tested and guarantee the highest audio quality.

The difference from similar systems depends on the great attention paid to the quality of the components (toroidal transformers, electrolytic capacitors, transistors and others) and to the efficiency of protections and limiter, all while always considering robustness, durability and safety of both internal circuitry and driven speakers.



PRODUCT DETAILS

Key features

Stereo/parallel/bridged-mono Modes

Intelligent Cooling System

2x 19" Rack Unit Chassis Design

AB-Class traditional and reliable circuitry

High-quality transformers and components

Thermal, Short Circuit and Signal Protection

Soft Start Function

Specifications

Stereo Rated Output Power (THD=0.5%, 1kHz, both channels driven) 2 x 300W @ 8Ω; 2 x 450W @ 4Ω

Bridged Output Power 1 x 900W @ 8Ω

Input Sensitivity 0.775V / 1.0V / 1.4V

Input Impedance 20KΩ / 10KΩ

Frequency Response 20Hz - 20kHz ± 0.3 dB

Damping Factor > 350

S/N Ratio > 95dB

Amplifier Class A/B

Power Requirements 230-250Vac - 50/60Hz

Power Consumption (average/max) 200W / 310W

Dimension (WxHxD) 483 x 340 x 88 mm (19.0 x 13.4 x 3.5 in)

Height 2 x 19" Rack Unit

Unit Weight 12.10 kg - 26.7 lbs.

Packing Size (WxHxD) 550 x 405 x 168 mm (21.6 x 15.9 x 6.6 in)

Carton Weight 13.85 kg - 30.5 lbs.