

LIVEO-530 BTBK

5.25" 2-Way Active Wall-Mount Speaker Pair with BT control, Black

The new LIVEO BT series combines the simplicity, elegance and ease of installation – already characteristic of the previous passive series – with the flexibility of active wireless systems. Thanks to the innovative state-of-the-art **Bluetooth wireless technology**, it is now possible to manage a higher number of speakers compared to the only two allowed until now by normal Bluetooth technology; the only limit is **25-30m distance** from the transmitter and that's it. It is then possible to make a small-to-medium-sized audio system even without any low-impedance connection or constant voltage line; just make sure that mains power is available.

The housing, with minimalist and elegant lines, is made of Polypropylene with **UV-resistant treatment**; this ensures robustness and greater durability to exposure to sun, moisture and rain. Plastic woofer, Mylar tweeter and plastic cover of rear connections make these speakers completely waterproof. Both transducers are selected to offer not only waterproofness and high durability, but also an excellent level of audio quality. Each Liveo series speaker, in order to simplify installation as much as possible, comes with both a **"C" bracket and a "ball-shaped" bracket**, both with adjustable horizontal and vertical positions











PRODUCT DETAILS

Key features

Nay Active Speakers
ass-D Power Amplifier with 20W Powers
25" Waterproof Woofer and 0.5" Mylar Dome Tweeter
ılti-Point BT connection with 16 system ID
, Stereo AUX input for all transmitters and speakers
ereo AUX output on transmitters
ack Finish
-Resistant PP Housing
rizontal and Vertical adjustable C-Bracket and Ball-Shaped bracket
curity Wire included
intable Housing and Grille



Specifications

Speaker Type	2-way Active
Built-in Amplifier	15W RMS - 20W Nominal
Frequency Response (-10dB)	100Hz-20kHz
Sensitivity (1W @ 1m)	85dB
Maximum SPL (peak)	100dB
Woofer	5.25" (135mm), PP cone
Woofer Impedance	8ohm
Tweeter	0.5" (13mm), Mylar dome
Crossover Frequency	3.5kHz
Bluetooth Transmitting/Receiving Distance	30m
Housing	UV-Resistant PP, paintable
Controls	Level /Data Entry Knob, 4-way DIP switch
Led Indicators	Led 1 (Mode), Led 2 (Status)
Connectors	1/8" Stereo Jack (AUX In), Power Input
Enclosure Material	ABS
Bracket	C-Bracket and Ball-shaped Bracket with Pan/Tilt adjustable
	angles and stainless-steel screws
Grille	Perforated aluminum, powder coated paint, acoustic
	transparent, paintable
Color	Black
Product Size - No Bracket (WxDxH)	156 x 156 x 227 mm (6.1 x 6.1 x 8.9 inch)
Speaker Weight (single unit, no bracket)	2.2kg
Packing Size (WxDxH) (pair)	420 x 195 x 255 mm (16.5 x 7.7 x 10 inch)
Packing Weight (pair)	5.6kg (12.35 lbs.)