# LIVEO-530 BTWH

## 5.25" 2-Way Active Wall-Mount Speaker Pair with BT control, White

The new LIVEO BT series combines the simplicity, elegance and ease of installation – already characteristic of the previous passive series – with the flexibility of active wireless systems. Thanks to the innovative state-of-the-art **Bluetooth wireless technology**, it is now possible to manage a higher number of speakers compared to the only two allowed until now by normal Bluetooth technology; the only limit is **25-30m distance** from the transmitter and that's it. It is then possible to make a small-to-medium-sized audio system even without any low-impedance connection or constant voltage line; just make sure that mains power is available.
The housing, with minimalist and elegant lines, is made of Polypropylene with **UV-resistant treatment**; this ensures robustness and greater durability to exposure to sun, moisture and rain. Plastic woofer, Mylar tweeter and plastic cover of rear connections make these speakers completely waterproof. Both transducers are selected to offer not only waterproofness and high durability, but also an excellent level of audio quality.
Each Liveo series speaker, in order to simplify installation as much as possible, comes with both a **"C" bracket and a "ball-shaped" bracket**, both with adjustable horizontal and vertical positions.
*NOTE: Liveo BT series Bluetooth technology works only in combination with its specific transmitter **Liveo-BT TX**











# PRODUCT DETAILS

## Key features

| |
|---|
| 2-Way Active Speakers |
| Class-D Power Amplifier with 20W Powers |
| 5.25" Waterproof Woofer and 0.5" Mylar Dome Tweeter |
| Bluetooth technology integrated (only with use of the Liveo-BT TX Multipoint Transmitter) |
| Multi-Point BT connection with 16 system ID |
| BT, Stereo AUX input for all transmitters and speakers |
| Stereo AUX output on transmitters |
| White Finish |
| UV-Resistant PP Housing |
| Horizontal and Vertical adjustable C-Bracket and Ball-Shaped bracket |
| Security Wire included |
| Paintable Housing and Grille |

## Specifications

| | |
|---|---|
| **Speaker Type** | 2-way Active |
| **Built-in Amplifier** | 15W RMS - 20W Nominal |
| **Frequency Response (-10dB)** | 100Hz-20kHz |
| **Sensitivity (1W @ 1m)** | 85dB |
| **Maximum SPL (peak)** | 100dB |
| **Woofer** | 5.25” (135mm), PP cone |
| **Woofer Impedance** | 8ohm |
| **Tweeter** | 0.5” (13mm), Mylar dome |
| **Crossover Frequency** | 3.5kHz |
| **Bluetooth Transmitting/Receiving Distance** | 30m |
| **Housing** | UV-Resistant PP, paintable |
| **Controls** | Level /Data Entry Knob, 4-way DIP switch |
| **Led Indicators** | Led 1 (Mode), Led 2 (Status) |
| **Connectors** | 1/8” Stereo Jack (AUX In), Power Input |
| **Enclosure Material** | ABS |
| **Bracket** | C-Bracket and Ball-shaped Bracket with Pan/Tilt adjustable angles and stainless-steel screws |
| **Grille** | Perforated aluminum, powder coated paint, acoustic transparent, paintable |
| **Color** | White |
| **Product Size - No Bracket (WxDxH)** | 156 x 156 x 227 mm (6.1 x 6.1 x 8.9 inch) |
| **Speaker Weight (single unit, no bracket)** | 2.2kg |
| **Packing Size (WxDxH) (pair)** | 420 x 195 x 255 mm (16.5 x 7.7 x 10 inch) |
| **Packing Weight (pair)** | 5.6kg (12.35 lbs.) |