

# LIVEO-640 BTWH

## 6.5" 2-Way Active Wall-Mount Speaker Pair with BT control, White

The new LIVEO BT series combines the simplicity, elegance and ease of installation - already characteristic of the previous passive series - with the flexibility of active wireless systems. Thanks to the innovative state-of-the-art **Bluetooth wireless technology**, it is now possible to manage a higher number of speakers compared to the only two allowed until now by normal Bluetooth technology; the only limit is **25-30m distance** from the transmitter and that's it. It is then possible to make a small-to-medium-sized audio system even without any low-impedance connection or constant voltage line; just make sure that mains power is available.

The housing, with minimalist and elegant lines, is made of Polypropylene with **UV-resistant treatment**; this ensures robustness and greater durability to exposure to sun, moisture and rain. Plastic woofer, Mylar tweeter and plastic cover of rear connections make these speakers completely waterproof. Both transducers are selected to offer not only waterproofness and high durability, but also an excellent level of audio quality. Each Liveo series speaker, in order to simplify installation as much as possible, comes with both a **"C" bracket and a "ball-shaped" bracket**, both with adjustable horizontal and vertical positions.



## PRODUCT DETAILS

### Key features

2-Way Active Speakers

Class-D Power Amplifier with 30W Nominal Power

6.5" Waterproof Woofer and 1" Silk Dome Tweeter

Multi-Point BT connection with 16 system ID

BT, Stereo AUX input for all transmitters and speakers

Stereo AUX output on transmitters

White Finish

UV-Resistant PP Housing

Horizontal and Vertical adjustable C-Bracket and Ball-Shaped bracket

Security Wire included

Paintable Housing and Grille

## Specifications

<b>Speaker Type</b>	2-way Active
<b>Built-in Amplifier</b>	25W RMS - 30W Nominal
<b>Frequency Response (-10dB)</b>	70Hz-20kHz
<b>Sensitivity (1W @ 1m)</b>	86dB
<b>Maximum SPL (peak)</b>	106dB
<b>Woofer</b>	6.5" (165mm), PP cone
<b>Woofer Impedance</b>	8ohm
<b>Tweeter</b>	1" (25mm), Silk dome
<b>Crossover Frequency</b>	2.0kHz
<b>Bluetooth Transmitting/Receiving Distance</b>	30m
<b>Housing</b>	UV-Resistant PP, paintable
<b>Controls</b>	Level /Data Entry Knob, 4-way DIP switch
<b>Led Indicators</b>	Led 1 (Mode), Led 2 (Status)
<b>Connectors</b>	1/8" Stereo Jack (AUX In), Power Input
<b>Enclosure Material</b>	ABS
<b>Bracket</b>	C-Bracket and Ball-shaped Bracket with Pan/Tilt adjustable angles and stainless-steel screws
<b>Grille</b>	Perforated aluminum, powder coated paint, acoustic transparent, paintable
<b>Color</b>	White
<b>Product Size - No Bracket (WxDxH)</b>	191 x 193 x 280 mm (7.5 x 7.6 x 11 inch)
<b>Speaker Weight (single unit, no bracket)</b>	3.2kg
<b>Packing Size (WxDxH) (pair)</b>	492 x 233 x 303 mm (19.4 x 9.2 x 12 inch)
<b>Packing Weight (pair)</b>	7.9kg (17.42 lbs.)