

GALA-630XW

6.5" 2-Way Coaxial Ceiling Speaker

GALA X Series offers powerful and accurate coaxial loudspeakers with woofer diameters ranging from 5,25" to 8", and powers from 20W to 40W RMS. They can be used with standard 70/100V professional amplifiers, and provide transparent and brilliant sound. They are therefore suitable for any application of music distribution at higher volume levels. The housing of GALA X speakers is made of high quality ABS. They also feature 0.5" Mylar-dome tweeters, polypropylene enforced woofers, and aluminum removable grille, which make these speakers suitable for humid environments. Installation is very easy, thanks to the quick mounting system with 4 screws. These screws are hidden behind the grill, and offer an elegant and minimalist design. The built-in line transformers allow the use with 70/100V lines, and offer two power taps to better adapt to different speaker arrangement and amplifier powers. They come in white color, but can be painted in any color.











PRODUCT DETAILS

Key features

-Way Coaxial Loudspeaker
uitable for Humid Environments
5" (165 mm) Woofer
DW RMS Power
igh Excursion Polypropylene Woofer
ylar-dome Precision Tweeter
uilt-in 70/100V Line Transformer
uick Mounting System
aintable Grille and Frame



Specifications

70	
ine Voltage 70\	V/100V
ine Transformer Bui	ilt-in, 2 power taps
00V Power 15\	W/30W
0V Power 7.5	5W/15W
requency Response (-10dB) 678	Hz-18.5kHz
ensitivity (1w/1m) 886	dB
loofer 6.5	5" (165mm), PP cone
weeter 0.5	5" (13mm), Mylar dome
ousing PP,	, paintable
P Rate (speaker installed) IP5	54
lounting Qui	rick mounting system with 4 screws
rille Per	rforated steel with acoustic transparent foam inside,
pai	intable
olor Wh	nite
utout Size Ø 2	202 mm
roduct Size (WxDxH) Ø 2	233 x 95 mm
peaker Weight 1.2	26 kg
acking Size (WxDxH) 238	8 x 100 x 238 mm
acking Weight 1,4	4 kg