

2-Way Open-Ceiling Speaker

The high level sound quality is assured thanks to the coaxial transducer with 5.25" (135mm) polypropylene woofer and 1" (25mm) Tweeter with Titanium dome. The integrated line transformer allows the use with 70/100V lines and offers 4 powers + low-impedance, to better adapt to different speaker configurations and amplifier powers. Housing finish is white, but can be painted in any color.



PRODUCT DETAILS

Key features

2-Way Coaxial Loudspeaker

Suitable for very-high open ceilings

Coaxial Transducer with 5.25" (135mm) Polypropylene Woofer

1" (25mm) Tweeter with Titanium Dome

40W RMS Power

Built-in 70/100V Line Transformer with 4 Power taps + 8ohm

Extremely Safe Hanging System

Paintable Housing and Grille

Specifications

Speaker Type	2-Way Passive, Coaxial
Line Voltage	70V / 100V
Line Transformer	Built-in, 4 power taps (+ 8ohm)
RMS Power	40W @ 8ohm
Frequency Response (-10dB)	65Hz-20kHz
Sensitivity (1w/1m)	90dB
Woofer	5.25" (135mm), Polypropylene cone
Tweeter	1" (25mm), Titanium dome
Housing	ABS, paintable
Mounting	M8 (1 on rear; 1 on side)
Grille	Perforated steel with acoustic transparent foam inside, paintable
Color	White
Product Size (WxDxH)	Ø 195 x 250 mm
Speaker Weight	2.4 kg
Packing Size (WxDxH)	230 x 230 x 270 mm
Packing Weight	3 kg