ONDA-B630W

30W 70V/100V 6.5" 2-Way Ceiling Speaker with Back Can

ONDA BW Series offers powerful and accurate coaxial loudspeakers with woofer diameters ranging from 5,25” to 8”, and powers from 20W to 40W RMS. They can be used with standard 70/100V as well as low impedance (8 ohm) professional amplifiers and provide transparent and brilliant sound.
The presence of the back can with a front reflex port allows for an emphasis on the frequency response on the medium-low frequency range, giving a much warmer and more enveloping sound even in the absence of the acoustic box effect due to the ceiling, which is necessary in the case of traditional ceiling speakers.
The housing of GALA BW speakers is made of high-quality ABS. They also feature 0.5” Mylar-dome tweeters, polypropylene enforced woofers.
Installation is very easy, thanks to the quick mounting system with 4 screws. These screws are hidden behind the grill and offer an elegant and minimalist design. The built-in line transformers allow use with 70/100V lines and offer three power taps plus 8ohm to better adapt to different speaker arrangement and amplifier powers. They come in white color but can be painted in any color.

PRODUCT DETAILS

Key features

2-Way Coaxial Loudspeakers
Lightweight but Sturdy Frame with back can
6.5” PP Woofer
0.5” Mylar Dome Tweeter
30W RMS Power
Built-in 70/100V Line Transformer
Front selection with 3 Taps, 8 ohms and Off
Quick-Fit Mounting System
Angle Coverage 120°

Specifications

RMS Power	30W
LF Transducer	5.25” Polypropylene Woofer
HF Transducer	0.5” Tweeter, Mylar Dome
Line Transformer	70/100V
Tapping Powers	30W-15W-7.5W-OFF-8OHM (100V), 30W-15W-7.5W-3.75W-OFF-8OHM (70V)
Frequency Range	50Hz – 20kHz
Sensitivity	90dB (1W@1m)
Cutting Ø	232.00 mm (9.13”)
Speaker Size	Ø260.00 x 186.50 mm (Ø10.23” x 7.34”)
Speaker Weight	1.88kg (4.14 lbs.)
Packing Size (WxDxH)	265 x 265 x 200 mm (10.43 x 10.43 x 7.87 inches)
Packing Weight	1,5kg (3.30 lbs.)