

# SONIX M0808D

8In-8Out DSP Audio Matrix with built-in 8x8 Dante™ Channels

The SoniX M0808D digital matrix, thanks to its powerful and flexible hardware and software architecture, is designed to be the heart of multi-zone audio systems for various types of installations. Its sophisticated processing, the quality of the AD and DA converters, the presence of a built-in card with 8 additional DANTE™ digital inputs and outputs, the advanced audio processing features with patented algorithms including Echo Cancellation, Feedback Suppression, Noise Suppression, and Automatic Gain, the 8 GPIO ports for integration with other equipment, and the powerful PC control software make it suitable for both conference solutions and multi-zone systems with up to 16 sources and 16 outputs.



## PRODUCT DETAILS

### Key features

- Analog Device SHARC® chipset
- Capacity up to 400MIPS, 1600MFLOPS
- 32-bit and 40-bit Floating-Point Processing
- Full Channel Audio Signal Matrix
- 8 Line/Mic Inputs x 8 Analog Outputs
- Built-in Dante™ 8x8 Channels
- AEC (Echo Cancellation), AFS (Feedback Suppression)
- ANS (Noise Suppression), AGC (Automatic Gain),
- Auto Mixer, Ducker function
- 12 band PEQ, 1200ms Delay & Limiter on Outputs
- 8x GPIO ports
- 16 Presets for recall
- USB Audio Player/Recorder
- Support Camera Tracking

## Specifications

<b>Processor</b>	ADI SHARC 21489(x2)
<b>Sampling rate/Digitalizing bit</b>	48K/24bit
<b>Input Gain</b>	from 0dBu to 48 dBu
<b>Phantom Power</b>	48V
<b>Frequency Response</b>	20~20KHz $\pm$ 0.3dB
<b>Maximum Level</b>	+18dBu
<b>THD + Noise</b>	0.003%@4dBu
<b>Input Dynamic Range</b>	110dB
<b>Output Dynamic Range</b>	112dB
<b>Background Noise (A-weighted)</b>	-91dB
<b>Common Mode Rejection Ratio @60Hz</b>	80dB
<b>Channel Isolation @1KHz</b>	108dB
<b>Input Impedance (Balanced Connection)</b>	5.4K $\Omega$
<b>Output Impedance (Balanced Connection)</b>	600 $\Omega$
<b>System Delay</b>	<3ms
<b>Working Power</b>	AC110~240V 50Hz-60Hz
<b>Maximum Power Consumption</b>	<40W
<b>Dimensions (WxDxH)</b>	482 x 260 x 45mm (19 x 10.2 x 1.8 in)
<b>Shipping Weight</b>	4Kg – 8.8 lbs.